

Exp. 5

7

10
Sub E1
cla

~~2.
22
11~~

22
7,
A

22
7,
A

22
7

22
7

5.

5.

a

3 Sub E1
a Cont. ²²
claim ²² 1, wherein each of differences in dielectric constants of said two or more powder coatings is 0.20 or less.

a 5 6. The combination of powder coatings according to claim ²² 1, wherein each of ratios of the electric resistance of said two or more powder coatings is from 0.1 to 10.

10 7. The combination of powder coatings according to claim ²² 1, wherein at least one powder coating is a white powder coating containing a white pigment, and the remaining powder coatings comprise no white pigments.

15 8. A powder coating composition usable in a powder coating method for forming a coating film having visually homogeneous hue, wherein said ¹⁷ powder coating composition comprises two or more powder coatings selected from the combination of any one of claims 1 to 7.

20 9. A coating method for forming a coating film having visually homogeneous hue, comprising the step of applying onto a substrate to be coated two or more powder coatings of which each color is different, wherein each of differences in triboelectric charges of said two or more
25 powder coatings is 5.0 $\mu\text{C/g}$ or less.

00045599-03499
"2655" 03499

10. The coating method according to claim 9, wherein each of differences in true specific gravities of said two or more powder coatings is 0.15 g/cc or less.

5 11. The coating method according to claim 9, wherein each of differences in apparent densities of said two or more powder coatings is 0.020 g/cc or less.

10 12. The coating method according to claim 9, wherein each of differences in softening points of said two or more powder coatings is 5.0°C or less, the softening points being measured using a capillary rheometer.

15 13. The coating method according to claim 9, wherein each of differences in dielectric constants of said two or more powder coatings is 0.20 or less.

20 14. The coating method according to claim 9, wherein each of ratios of the electric resistance of said two or more powder coatings is from 0.1 to 10.

25 15. The coating method according to claim 9, wherein at least one powder coating is a white powder coating containing a white pigment, and the remaining powder

08815592 "031297"

coatings comprise no white pigments.

16. A coating method for forming a coating film having visually homogeneous hue, comprising the steps of
5 applying a white coating on a substrate to be coated, to give a substrate coated with the white coating; and then applying thereon two or more powder coatings of which each color is different, wherein each of differences in triboelectric charges of said two or more powder coatings
10 is 5.0 $\mu\text{C/g}$ or less.

17. The coating method according to claim 16, wherein each of differences in true specific gravities of said two or more powder coatings is 0.15 g/cc or less.

18. The coating method according to claim 16, wherein each of differences in apparent densities of said two or more powder coatings is 0.020 g/cc or less.

19. The coating method according to claim 16, wherein each of differences in softening points of said two or more powder coatings is 5.0°C or less, the softening points being measured using a capillary rheometer.

20. The coating method according to claim 16, wherein each of differences in dielectric constants of said two or more powder coatings is 0.20 or less.

5 21. The coating method according to claim 16, wherein each of ratios of the electric resistance of said two or more powder coatings is from 0.1 to 10.

Add A)

Add β'

Add E8

00015592 031297
/6210 26551880